



Garage Door Operators S-S-F-S-S





Two MIDI-handsets shipped as standard



One wall holder is supplied as standard



The optional MINI-handset compared to the standard MIDI-hand transmitter



The Digi-Pad - a highly convenient extra.



Replacement components, i.e. Printed Circuit Boards, Transformers etc. are easily exchanged and widely available. In the unlikely event of failure, with Seip there is no need to purchase a costly motor head


Why SEIP should be your Automatic Choice?

The TS series offers only quality components: powerful motors with self locking gears and electronics designed and manufactured in Germany. We are one of few manufacturers using quality galvanized steel with a thickness of 2.5 mm to assure the highest mechanical strength.

The stirdy design of the TS-series is highly efficient.

We have confidence in our products, backed up by our five year manufacturer's warranty. In support of this claim, our products are running on permanent test. On our test stands, operators run 24 hours a day, 365 days of the year to check and prove the strength and reliability of components. Under stringent test conditions, we reach a minimum of 60,000 cycles, moving weights up to 100 kg.

And finally, SEIP UK LTD prides itself not only on its superb range of quality products, but with providing all customers with a back up service second to none!





Modul "AZ": provides advanced features for automatic closing. Fast-closing after passing the photo-cell or fixed closing times from 10 to 240 seconds adjustable.



Modul "GT": provides either separated impulses for opening and closing operations OR a partial opening feature which is handy for side-running sectional doors.



Our door operators are being tested for safety standards in our factory testing stands with different types and sizes of garage doors.



| Technical Data | TS 75 | TS 100 |
|--------------------------------------|------------------------|------------------------|
| Maximum Pulling Force (adjustable) | 75 kg | 110 kg |
| Maximum Peek Force | 85 kg | 115 kg |
| Force-Setting for Operation | Automatic | Automatic |
| Running Speed (max.) | 14.5 cm/sec. | 14.5 cm/sec. |
| Speed in Soft-Mode | 8 cm/sec. | 8 cm/sec. |
| Closing Speed (max./min. adjustable) | 6 to 14.5 cm/sec. | 6 to 14.5 cm/sec. |
| Automation of Side Hinged Doors | Adjustable | Adjustable |
| Integrated Lighting | 230V AC, max. 40 Watts | 230V AC, max. 40 Watts |
| Adjustable Light Duration | 80 to 240 sec. | 80 to 240 sec. |
| Blinking Pre-Warning Light | Adjustable | Adjustable |
| Max. Number of Remotes | 256 | 256 |
| Power Consumption in Stand-By | 2.0 watts | 2.0 watts |
| Power Supply | 190-250V AC | 190-250V AC |
| Net Running Length | 2,345 mm | 2,345 mm |
| Overall Length | 3.150 mm | 3.150 mm |
| Minimum Space above the Door | 35 mm | 35 mm |
| Max. Running Length with Extension | 3.850 mm | 3.850 mm |
| · | | |

All data is subject to technical alterations!



